Fire Fighting Foam

Product #697

Aqueous film-forming foam

This non-corrosive synthetic concentrate produces a long-lasting and dense foam designed for fighting Class A and Class B fires. It offers superior water retention, while promoting smothering, cooling and vapor suppression capabilities. Designed for use at 3% dilution, it's compatible to use with surfactants and tank protectors.

Use on Class A and Class B fires:

- Non-polar liquids
- Gasoline
- Fuel Oil

- Mineral Spirits
- Benzene
- Other Hydrocarbons

Features and Benefits

- Excellent smothering and vapor suppressing properties.
- Designed for use on Class A and Class B flammable liquid fires.
- Cools the fuel and adjacent surfaces to below their ignition temperatures.

Properties

Fragrance..... Detergent Yes Concentrate..... Specific gravity...... 1.03 9.5-10.5 pH.....

Directions Complete directions on product label

For Class A and Class B fires, involving, dilute to 3% using a standard eductor or other proportioning system. May also be premixed.

Active Ingredients

Active Ingredients	CAS Number
Water	7732-18-5
Diethylene glycol monobutyl ether	. 112-34-5
Sodium Lauryl Sulfate	73296-89-6
Ethylene Glycol	407.04.4
Coconut Diethanolamide	. 68603-42-9

Caution: May cause eye and skin irritation. Keep out of the reach of children.

DOT Shipping (ground transportation)

Proper Shipping Name: None None Class: None ID Number: None Packing Group:

NFPA RATINGS Flammability



Quantities

30, 35 & 55 gallon 5 or 6 gallon 6 X 1 gallon 4 X 1 gallon